

IN THE CLAIMS

Please amend the claims to read as indicated herein.

Please cancel claim 5.

1. (currently amended) A measurement unit for use in a measuring setup for measuring an optical device under test (DUT), comprising:
 - a fiber connection for connecting to said DUT;
 - an optical circuit for providing an optical signal from and/or to the DUT via said fiber connection;
 - a shielding unit having an upper casing part and a lower casing part, for holding the optical circuit therein and for providing at least a partial shielding of the optical circuit against mechanical noise;
 - a vibration absorption device for absorbing vibrations of the shielding unit; and
 - a DUT holding device, situated on top of the shielding unit, for holding the DUT.
2. (previously presented) The measurement unit of claim 1, wherein the shielding unit has a relatively high weight, thus rendering the shielding unit less susceptible excitation by mechanical vibrations.
3. (previously presented) The measurement unit of claim 1, wherein the shielding unit weighs substantially more than the optical circuit.
4. (previously presented) The measurement unit of claim 1, wherein the shielding unit comprises a mass plate or is provided of a material massive relative to the optical circuit.
5. (canceled)
6. (previously presented) The measurement unit of claim 1, wherein the optical circuit is attached to a part of the shielding unit.

7. (previously presented) The measurement unit of claim 1, further comprising a vibration damping or shielding device between the optical circuit and the shielding unit.

8. (previously presented) The measurement unit of claim 1, wherein the optical circuit comprises an interferometer.

9. (canceled)

10. (previously presented) The measurement unit of claim 1, wherein the DUT holding device is coupled to the shielding unit so that the shielding unit provides at least a partial shielding of the DUT against mechanical noise.

11. (previously presented) The measurement unit of claim 1, wherein the DUT holding device is outside the shielding unit.

12. (canceled)

13. (previously presented) The measurement unit of claim 1, wherein the vibration absorption device comprises an arrangement of resilient and plastic members for damping and absorbing mechanical vibrations.

14. (previously presented) The measurement unit of claim 1, wherein the optical circuit comprises components that provide substantially no vibration during the measuring step.

15. (currently amended) A measuring setup for measuring an optical device under test (DUT), comprising:

an optical signal source for applying an optical signal to the DUT;

an optical receiver unit for measuring a response of the DUT to the applied signal; and

a measurement unit coupled between the optical signal source and the optical receiver unit,

said measurement device having:

a fiber connection for connecting to said DUT;
an optical circuit for providing an optical signal from and/or to the DUT via
said fiber connection;
a shielding unit having an upper casing part and a lower casing part, for holding
the optical circuit therein and for providing at least a partial shielding of
the optical circuit against mechanical noise;
a vibration absorption device for absorbing vibrations of the shielding unit; and
a DUT holding unit, situated on top of the shielding unit, for holding the DUT.

16. (previously presented) The measurement unit of claim 7, wherein said vibration
damping or shielding device is a rubber sheet.

17. (canceled)